

**Reliability****Flexibility****Easy to use**

- External SIM card slot, easier for SIM card replacement
- Metal body, beautiful and long durable
- Plug and play 1s installation, no need to set
- Easy to configure with App “Aarushasmartenergy”
- Support local and remote monitoring
- IP65, for both indoor and outdoor installation
- External antenna, stronger signal and reliable communication
- Enable mobile monitoring at anytime anywhere

**General Data**

Max. No. of Inverters	1
Inverter Communication	USB3.0
External Antenna	SMA water-proof glue stick antenna
Data Intervals	2Min
Preference Setting	Remote Web, APP
Firmware Upgrade	Wireless upgrade
Data Access	Remote server
Working Voltage	DC 5V
Working Current	50mA(600mA Peak)

**Wireless Data**

Wireless Transmitting Power	GSM850/EGSM900:5dbm~32.5dbm, DCS1800/PCS1900:0dbm~29.5dbm
Wireless Receiving Sensitivity	<-108.5dBm
Wireless Operating Frequency	GSM850, EGSM900, DCS1800, PCS1900
GPRS Connection Features	GPRS multi-slot class is 10 (default), GPRS mobile station class B

**Environmental Data**

Operating Temperature(°C)	-10~+60
Operating Humidity	0%-90% relative humidity, no condensation
Storage Temperature(°C)	-40~+85
Storage Humidity	<40%
Protection Degree	IP65

**Other Data**

Dimensions(L*W*H)	156*52*30mm
Weight	140g
Certificates	SRRC
Warranty	2 years

