



Aarusha Smart Energy LLP
Office No. 316, Binali Complex,
Naranpura, Ahmedabad -13, Gujarat, India.
Tel: +91-79-27490041/42.
E: info@aarushaenergy.com
www.aarushaenergy.com

Smart Series Home Wallbox

Innovative

- Trendy streamline design
- One-step installation
- Activated by NFC
- Provide smart App as a charging partner

Flexible

- Wall-mount/Floor-stand
- 14-50P/6-50P NEMA input plugs
- Three enclosure colors
- Multiple charging modes

Compatibility

- Type 1 connector for American market
- Interoperable with all major automobiles in North American market
- OCPP 1.6 Json standard protocol

Secure and safe

- Anti-welding protection
- NEMA4 (IP66) dustproof and waterproof design
- CCID 20 leakage current protection
- UL listed and certified with the highest standards for electrical safety

Pearl White



Emerald Green



Space Black



NEMA 14-50P



NEMA 6-50P





Aarusha

Aarusha Smart Energy LLP
 Office No. 316, Binali Complex,
 Naranpura, Ahmedabad -13,Gujarat, India.
 Tel: +91-79-27490041/42.
 E: info@aarushaenergy.com
 www.aarushaenergy.com

Smart Series Home Wallbox

Datasheet	Model	AC010K-AU-35S	AC010K-GU-35S
Input	Power Supply	Single Phase	
	Rated Voltage	240V AC	
	Rated Current	40A	
	Frequency	60Hz	
	Maximum Current	40A	
	Plug	NEMA 14-50P	NEMA 6-50P
Output	Output Power	9.6kW	
	Charge Outlet	Type 1	
	Cable Length	7.5m (25feet)	
User Interface	Housing Material	Plastic PC	
	LED Indicator	Green/Yellow/Red	
	Start Mode	Plug&Play/RFID/NFC/APP	
Communication	WiFi	Yes	
	Ethernet	Yes	
	Bluetooth	Yes	
Secure and Safety	Leakage Current Protection	CCID 20	
	Enclosure Rating	NEMA 4	
	Electrical Protection	Over current protection, Residual Current protection, Surge protection, Ground Protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection	
	Certification Standard	CSAus/FCC/IC/Energy Star/BQB	
Environment	Limited Warranty	2 years	
	Installation	Wall-mount/Pole-mount (Optional)	
	Work Temperature	-30°C~+50°C	
	Work Humidity	5%~95%	
	Work Altitude	<2000m	
Package	Product Dimension	344*192*100mm(H*W*D)	
	Package Dimension	430*330*315mm(H*W*D)	
	Net Weight	6.0kg	
	Gross Weight	8.0kg	
	External Package	Carton	



Note : The specifications included in this datasheet are subject to change without notice.